

FoCaLiZe

Mixing Programs and Proofs

François Pessaux - ENSTA ParisTech (U2IS)

francois.pessaux@ensta-paristech.fr

PARKAS Seminar
26 May 2014

Topics and Short Outline

- FoCaLiZe: a language to express **code**, **properties** and **formal proofs**.
- Outline:
 - Short presentation of FoCaLiZe,
 - How **design & features** choices drive the **semantics** and the **compilation model**,
 - Sketch of compilation scheme focusing on **dependencies**.

Started more than 10 years ago (T. Hardin and R. Rioboo) ...

FoCaLiZe *Credo*

- Why ?
 - Standards require usage of formal methods to ensure high level assurance of critical systems.
 - Formal methods ? Runtime verification, UML ... For us: **mechanically checked proofs**.
 - Ideally should be within **any** computer science engineer skills: our long term goal.
- How ?
 - Basis: wedding OCaml and Coq **avoiding** too complex features.
 - Features **mixing logical and programming** aspects: inheritance, late-binding, abstraction, parametrisation, **properties** and **proofs**.
 - Mixing **computational/logical** features: risk of **inconsistencies** (S. Boulmé PhD) .
 - Our claim: **Accepted** by FoCaLiZe compiler $\Rightarrow$ **No** OCaml or Coq error!

FoCaL: first compiler by V. Prevosto ... FoCaLiZe: Darwinian evolution

« Why should I Burden Myself with FoCaLiZe? »

- (*) **Code** and **properties** not compiled separately.
- **Data-types** and **properties** both seen as Coq **types**.
- **Definitions** and **theorems** considered the **same** way.
- ➔ More confidence in « *what is proved is (quite) what is ran* ».
- Proofs directly in Coq ? Requires specific user skills.
- ➔ **Dedicated** language: **independence** from logical target language.
- ➔ **Hierarchical** proof structure: **human** readable.
- ➔ Use of **Zenon automated theorem prover**: reduces the user's burden.
- * : reveals usually implicit **dependencies**.
- No errors from target languages: ensure no missing « stuff one **depends on** ».
- Get compact code for traceability: minimize **dependencies**.

Semantical Framework

- **Requirements / implementation**: a single language and a single semantics for **logical / programming** features.
- **Pure functional** declarations and definitions, **first-order** (like) formulae, proofs written in *FPL*.
- Properties can use function names only, proofs can unfold function definitions **not the inverse**.
- Thus a kind of **dependent type theory**, however some **dependencies** are forbidden: don't want/need the whole Coq's power.
- FoCaLiZe source: compiled to **OCaml** and **Coq source** files.
- Proofs sent to **Zenon** returning a **Coq term** to **embed** in final Coq source.
- **Curry-Howard** isomorphism. Logical aspects **discarded** in **OCaml**.

Species

- Structure grouping **signatures**, **properties**, **functions** and **proofs** related to an underlying data-type: the **representation**.

```
species OrdData =  
  inherit Data ;  
  signature lt: Self -> Self -> bool ;  
  signature eq: Self -> Self -> bool ;  
  let gt (x, y) = ~~ (lt (x, y)) && ~~ (eq (x, y)) ;  
  property ltNotGt: all x y: Self, lt (x, y) -> ~gt (x, y) ;  
end ;;
```

- **Inheritance**: to enhance **reusability**.
- **Late-binding**: introduces a **name** and a **type**, deferring definition (representation also).
- Allows to **incrementally** introduce new items.
- Progression from a **specification** to **implementation**.
- At each step: use new items to prove **conformance** with **previously** stated **requirements**.

Parameterization

- Parameterized module ? We need **parameterized species**.
- Two kinds of parameters:
 - Use **methods** & **properties** of other species: **collection parameter**.
 - Use **values** of other species: **entity parameter**.

```
species IsIn (V is OrdData, minv in V, maxv in V) =  
  representation = (V * statut_t) ;  
  let filter (x) : Self =  
    if V!lt (x, minv) then (minv, Too_low)  
    else if V!gt (x, maxv) then (maxv, Too_high) ... ;  
  theorem lowMin: all x: V,  
    getStatus (filter (x)) = Too_low -> ~ V!gt(x, minv)  
  proof = ... ;
```

Abstracted or not (to be) Abstracted

- Definition of **representation** exposed or encapsulated ?
 - **Inheritance** & **late-binding** require **exposure**.
 - Parameterization requires **abstraction**.
- ➔ Visibility driven by 2 structures:
 - **Species**: total **transparency** of **definitions**.
 - **Collection**: representation **abstracted**, only **types** (hence also **properties**) visible.

Collection

- To provide **effective arguments** to collection parameters.
- No link-time errors $\Rightarrow$ all exported **functions** must be **defined**.
- No inconsistencies $\Rightarrow$ all **properties** must be **proved**.
- Abstracted « instance » of a **complete** species.
- The **only** form of **proved run-able** code.

```
species TheInt =  
  inherit OrdData ;  
  ... (* Complete species. *)  
end ;;  
collection IntC = implement TheInt ; end ;;  
collection In_5_10 =  
  implement IsIn (IntC, IntC!fromInt (5), IntC!fromInt (10)) ;  
end ;;
```

Properties and Proofs

- Be **independent** from any particular proof checker.
- **Own** proof language, **natural deduction** style.
- **Proof** = **hierarchical** decomposition into intermediate steps introducing **subgoals** and **assumptions**.
- **Leaf: subgoal** which can be **automatically** handled by **Zenon** automated prover using **facts** given by the **user**.

```
theorem t : all a b c : bool, a -> (a -> b) -> (b -> c) -> c
proof =
  <1>1 assume a b c : bool,
    hypothesis h1: a, hypothesis h2: a -> b, hypothesis h3: b -> c,
    prove c
  <2>1 prove b by hypothesis h1, h2
  <2>2 qed by step <2>1 hypothesis h3
<1>2 qed by step <1>1
```

- **Zenon** returns a **Coq term** plugged by the compiler in the context.
- **Only** acceptable Zenon errors: « *out of memory* », « *time out* », « *no proof found* ».

Outline of Coming Technical Points

Reminders about FoCaLiZe ended!

Coming next...

- **Dependencies** on **own** species methods
- **Dependencies** on **collection parameters** methods
- Code generation: **method generators**
- Code generation: **collection generators**
- Initial work: V. **Prevosto** dependency analysis, rules modified and extended.

Notion of Dependencies (1/3)

- A method **depending** on the **definition** of m has a **def**-dependency on m .
- Only two possible def-dependencies:

- **Proof** with a **by definition** of m (unfolds the definition of m)

➡ If m redefined, proof must be invalidated.

- **Functions** and **proofs** can def-depend on the **representation**.
- By **syntax**, functions cannot def-depend on proofs.
- By **encapsulation**, no possible def-dependencies on parameters methods.
- Analysis required to prevent def-dependencies on the **representation** in **properties** and theorems **statements**.

```
species Sample =  
  representation = bool ;  
  signature decldep_on_me : Self -> int;  
  property things_hold: all x : int, bla (i) ;  
  let defdep_on_me (x : Self) = ... if (x) decldep_on_me (x) else ... ;  
  theorem prove_me: all x : Self, all i : int, bla (i) \/ defdep_on_me (x) = i  
    proof = by definition of defdep_on_me property things_hold ;  
end ;;
```

Notion of Dependencies (2/3)

- A method **depending** on the **definition** of m has a **def-dependency** on m .
- Only two possible def-dependencies:
 - **Proof** with a **by definition** of m (unfolds the definition of m)
 - ➔ If m redefined, proof must be invalidated.
 - **Functions** and **proofs** can def-depend on the **representation**.
- By **syntax**, functions cannot def-depend on proofs.
- By **encapsulation**, no possible def-dependencies on parameters methods.
- Analysis required to prevent def-depend on the **representation** in **properties** and theorems **statements**.

```
species Sample =
```

```
representation = bool ;
```

```
signature decldep_on_me : Self -> int;
```

```
property things_hold: all x : int, bla (i) ;
```

```
let defdep_on_me (x : Self) = ... if (x) decldep_on_me (x) else ... ;
```

```
theorem prove_me: all x : Self, all i : int, bla (i) \ / defdep_on_me (x) = i
```

```
  proof = by definition of decldep_on_me property things_hold ;
```

```
end ;;
```

Notion of Dependencies (3/3)

- Method **depending** on the **declaration** of `m` has a **decl-dependency** on `m`.
- **Decl**-dependencies: a matter of **typechecking**.

```
species Sample =  
  representation = bool ;  
  signature decldep_on_me : Self -> int;  
  property things_hold: all x : int, bla (i) ;  
  let defdep_on_me (x : Self) = ... if (x) decldep_on_me (x) else ... ;  
  theorem prove_me: all x : Self, all i : int, bla (i) \/  
    proof = by definition of defdep_on_me property things_hold ;  
end ;;
```

- Dependencies: the **key** to ensure **no** OCaml/Coq **errors**!

Finding Dependencies on Methods of *Self*

- **Cyclic** dependencies only allowed between (mutually) **recursive** functions.
- Through **proofs**, **def**-dependencies force keeping **definitions** in the context to be typecheck-able (fact by definition of).
- ➔ These definitions **themselves** have to be **typecheck-able**.
- Through **proofs**, **decl**-dependencies on **logical** methods (expressions).
- ➔ Methods in such « **types** » **also** have to **typecheck-able**.

```
property ltNotGt: all x y: Self, lt (x, y) -> ~gt (x, y) ;
```

Coq ⇒

```
Theorem ltNotGt (abst_T : Set) (abst_lt := lt) (abst_gt := OrdData.gt abst_T abst_eq abst_lt) :  
  forall x y : abst_T, Is_true ((abst_lt x y)) -> ~Is_true ((abst_gt x y)).  
apply "Large Coq term generated by Zenon".
```

- Keep methods ∈ **transitive closure** of the **def**-dependency relation + methods on which these latter **decl**-depend: the **visible universe**.

Visible Universe

$$\frac{y \in \wr x \int_S}{y \in |x|} \quad \frac{y <_S^{def} x}{y \in |x|}$$

$$\frac{z <_S^{def} x \quad y \in \wr z \int_S}{y \in |x|} \quad \frac{z \in |x| \quad y \in \wr \mathcal{T}_S(z) \int_S}{y \in |x|}$$

- $x <_S^{def} y$: « y **def**-depends on x by transitivity »
- $\mathcal{T}_S(x)$: « the **type** of x in the species S ».

Minimal Typing Environment

$$\begin{array}{l} \emptyset \mathbin{\mathbb{M}} x = \emptyset \\[10pt] \frac{y \notin |x| \quad \{y_i : \tau_i = e_i\} \mathbin{\mathbb{M}} x = \Sigma}{\{y : \tau = e ; y_i : \tau_i = e_i\} \mathbin{\mathbb{M}} x = \Sigma} \\[10pt] \frac{y \in |x| \quad y <_S^{def} x \quad \{y_i : \tau_i = e_i\} \mathbin{\mathbb{M}} x = \Sigma}{\{y : \tau = e ; y_i : \tau_i = e_i\} \mathbin{\mathbb{M}} x = \{y : \tau = e ; \Sigma\}} \\[10pt] \frac{y \in |x| \quad y \not<_S^{def} x \quad \{y_i : \tau_i = e_i\} \mathbin{\mathbb{M}} x = \Sigma}{\{y : \tau = e ; y_i : \tau_i = e_i\} \mathbin{\mathbb{M}} x = \{y : \tau ; \Sigma\}} \end{array}$$

- Methods $\notin$ visible universe: **not** required.
- Methods $\in$ visible universe on which x **doesn't def**-depend: only their type required.
- Methods $\in$ visible universe on which x **def**-depends: their **type and body** required.

Dependencies Summary

- `type t ('a) = ...`
- `... (S * int) ...`
- `all x : t (int), y : S, f (x, S) ...`

- by type definition of ...
- On the representation:
`<2>1 assume x : Self, prove x = 0`

$\vdash$ <i>Peut dépendre de</i>	Type	Preuve	Définition
Type	✓		
Preuve	✓		✓
Définition	✓		✓

- by type u
- `all x : t (int), f (x) ...`
- by property ...

- `let f (x : S) = ...`
- `let g (x : Self) = ...`

- On the representation:
`let h (x : Self) = if x ...`

Dependencies on Methods of Collection Parameters

- Similar problem than methods of Self: track dependencies on **collection parameters methods**.

theorem too_low_not_gt_min:

all x : V, get_status (filter (x)) = Too_low -> ~ **V!gt** (x, minv)

proof = <...> ... bla ... prove ~ **V!gt** (x, minv) ... property **V!lt_not_gt** ... ;

Coq ⇒

```
Theorem too_low_not_gt_min (_p_V_T : Set) (_p_V_lt : _p_V_T -> _p_V_T -> basics.bool__t)
  (_p_V_gt : _p_V_T -> _p_V_T -> basics.bool__t)
  (_p_V_lt_not_gt : forall x y : _p_V_T, Is_true ((_p_V_lt x y)) -> ~Is_true ((_p_V_gt x y)))
  (_p_minv_minv : _p_V_T) (_p_maxv_maxv : _p_V_T) (abst_T := ((_p_V_T * statut_t__t)%type))
  (abst_filter := filter _p_V_T _p_V_lt _p_V_gt _p_minv_minv _p_maxv_maxv) ... := ... ;
```

- Again, AST traversal is **not** sufficient.
- Consider there are dependencies on all the methods of all the collection parameters?
➡ Cumbersome, unreadable, inefficient!
- Challenge: find the **minimal set** of required methods.

Computing Deps on Methods of Collection Parameters

- Four kinds of rules, collecting dependencies a method as on a parameter method...
 - (2) **explicitly** stated in the body (resp. type) of a definition,
 - (2) induced by the dependencies **the** method has inside **its** hosting species (for decl and def),
 - (1) because this parameter is used as **effective argument** to build the **current** parameter,
 - (1) due to decl-dependencies that methods **of parameters** have inside their **own** species and that are visible through **types**.
- Entity parameters: no extra dependencies since no methods. Are « *themselves the dependency* ».

Rules for Deps. on Parameters Methods (1/4)

$$\mathcal{DoP}_{[\text{BODY}]}(S, C)[x] = \mathcal{DoP}_{[\text{EXPR}]}(S, C)[\mathcal{B}_S(x)]$$

$$\mathcal{DoP}_{[\text{TYPE}]}(S, C)[x] = \mathcal{DoP}_{[\text{EXPR}]}(S, C)[\mathcal{T}_S(x)]$$

- [Body]: harvest dependencies on a method **explicitly stated** in the **body** of a definition.
- [Type]: harvest dependencies on a method **explicitly stated** in the **type** of a definition.

Rules for Deps. on Parameters Methods (2/4)

$$\mathcal{DoP}_{[\text{DEF}]}(S, C)[x] = \mathcal{DoP}_{[\text{EXPR}]}(S, C)[\mathcal{B}_S(z)] \quad \text{for all } z \text{ such as } z <_S^{def} x$$

$$\mathcal{DoP}_{[\text{UNIV}]}(S, C)[x] = \mathcal{DoP}_{[\text{EXPR}]}(S, C)[\mathcal{T}_S(z)] \quad \text{for all } z \text{ such as } z \in |x|$$

- [Def] and [Univ]: collect dependencies of **a method** on a parameter induced by the dependencies **this** method has in **its hosting** species.
- Note: methods z introduced by [Def] included in those introduced by [Univ] (*vis. univ. wider than only transitive def-deps and their related decl-deps*).

Rules for Deps. on Parameters Methods (3/4)

$$\begin{array}{c}
 \mathcal{E}(S) = (\dots, C_p \text{ is } \dots, \dots, C_{p'} \text{ is } S'(\dots, C_p, \dots)) \\
 \mathcal{E}(S') = (\dots, C'_k \text{ is } I'_k, \dots) \\
 z \in \mathcal{DoP}_{[\text{TYPE}]}(S, C_{p'})[x] \quad \vee \quad z \in \mathcal{DoP}_{[\text{BODY}]}(S, C_{p'})[x] \\
 (y : \tau_y) \in \mathcal{DoP}_{[\text{TYPE}]}(S', C'_k)[z] \\
 \hline
 (y : \tau_y[C'_k \leftarrow C_p]) \in \mathcal{DoP}_{[\text{PRM}]}(S, C_p)[x]
 \end{array}$$

- Harvest dependencies of a method on a **previous parameter C_p used as argument** to build the **current** parameter $C_{p'}$.
- Difference with previous rules: result is **not only** a set of names: **types** are **explicit**.

Because type of the methods of this set differs from the one computed during typechecking of the species used as parameter.

Rules for Deps. on Parameters Methods (4/4)

$$\frac{\mathcal{E}(S) = (\dots, C_p \text{ is } I_p, \dots) \quad z \in \mathcal{D}(S, C_p)[x] \quad (y : \tau_y) \in \mathcal{T}_{I_p}(z) \int_{I_p}}{(y : \tau_y[\text{Self} \leftarrow C_p]) \in \mathcal{D}^+(\mathcal{D}, S, C_p)[x]} \text{CLOSE}$$

- Take into account **decl**-dependencies that methods of parameters have inside **their own species** and that are visible through **types**.

```
species A =
  signature f : Self -> int ;
  signature g : Self -> int ;
  property th0: all x : Self, f (x) = 0 /\ g (x) = 1 ;
end ;;

species B (P is A) =
  theorem th1 : all x : P, P!f (x) = 0 proof = by property P!th0 ;
end ;;
```

Code Generation: Method Generators

- Starts after resolution of inheritance and late-binding, typing and dependency analysis.
 - For **traceability** and **assessment**: **common** code generation model OCaml / Coq.
 - Generate code for **only** collection? $\Rightarrow$ **no** code **sharing**.
 - Want to share methods bodies: reduces code **size** and assessment **duration**.
 - Method **m**: when defined $\Rightarrow$ emit its **method generator**:
 - compiled version of m's body,
 - methods **m decl**-depends on are **λ -lifted** (get rid of only declared symbols),
 - calls are replaced by these λ -lifted variables,
 - methods (**n**) **m def**-depends on are **not** λ -lifted: use of **n**'s method generator
 - ... **applied** to methods **n itself** has λ -lifted.
- $\Rightarrow$ Method generator **shared** along **inheritance** and between **collections** of a same species.

Code Generation: Method Generators (ended)

- Explicit polymorphism $\Rightarrow$ extra λ -lifts to introduce **representations** of *Self* and of parameters.
- Methods and representation can depend on representations and methods of **collection parameters**.
- $\Rightarrow$ λ -lifts of dependencies upon parameters : **outermost** abstractions to fit Coq's dependencies.
- Generated code grouped in a **module**.
- $\Rightarrow$ Enforce **modularity**.
- $\Rightarrow$ Benefit from a convenient **namespace** mechanism.

Code Generation: Collection Generators

- Code generation for collections: create **computational runnable** code and **checkable logical** term.
- Right version of the method generator: **last** definition in the inheritance tree.
- **Effective arguments** for method generator: retrieved from the species **hosting it** and **instantiations** of formal parameters done during **inheritance**.
- Apply separately each method generator to its effective arguments?
- ➔ **No** code sharing between **collections** issued from the **same** parameterized species.
- Share the **applications** of method generators to their arguments between **collections**: ↗ sharing.

Code Generation: Collection Generators (ended)

- Applications grouped into a **record** ... move λ -lifts of all parameters dependencies **outside** the record.
- The obtained function is a **collection generator**.
- Go further and replace λ -lifts by **one unique** abstracting the whole collection parameter?
 - ➔ **No**: would require **first-class** modules and **subtyping** in target languages!
Would reduce target languages candidates.
- Collection: obtained by **application** of its **generator** to get a **record** value.
- Methods of the collection: **picked** inside the **record** and surrounded by a **module**.

Conclusion

- **Design** and **feature choices** leading to an original compilation problem.
Computational and logical aspects handled together, flexible development constructs, readable proofs, traceable code, etc.
- Difficulty 1: **dependency calculus** for consistency and code generation.
- Difficulty 2: **common code generation** model for all target languages.
- Difficulty 3: create the **context** where to insert Zenon proof.
- Difficulty 4: ensure **no errors** are raised by target languages.
- And number of other ones not presented here!
Normal form, parameters instantiation, recursion & termination proofs, etc.

Thank you for your Attention

Some questions ?

I would like to thank:

- **Thérèse Hardin, Renaud Rioboo** (FoC's parents),
- **Damien Doligez** from INRIA / Microsoft Research (Zenon's dad),
- and other **folks** who gave advice and contribute to FoCaLiZe.

<http://focalize.inria.fr>