

Supplemental Material for “Online EM Algorithm for Hidden Markov Models” Published in the Journal of Computational and Graphical Statistics: MATLAB/OCTAVE Function Used for Implementing the Online EM Algorithm in Section 4

Olivier Cappé

LTCI, Telecom ParisTech & CNRS

## 1 Main Function: `ion_online`

```
function [q, mu, v] = ion_online(Y, q_0, mu_0, v_0, gam)

% ion_online    On-line EM algorithm for the ion channel model.
% Use: [q, mu, v] = ion_online(Y, q_0, mu_0, v_0, gam) where
%       Y:      observations (n x 1)
%       gam:    stepsizes (n x 1)
%       q_0:    initial estimate of transition matrix (m x m)
%       mu_0:   initial estimates of means (m x 1)
%       v_0:    initial estimate of variance (scalar)
% and
%       q:      estimated transition matrices (m x m x n+1)
%       mu:     estimated means (m x 1 x n+1)
%       v:      estimated variances (1 x 1 x n+1)
%
% m is the number of states and n the number of observations.

% Parameters
INHIBIT_LAG = 20;
% In inhibition stage, let gam(i) = 1/i and do not perform any update
gam(1:INHIBIT_LAG) = 1./(1:INHIBIT_LAG);

% Dimensions
n = length(Y);
m = length(mu_0);

% Initialization
q = zeros(m,m,n+1);
mu = zeros(m,1,n+1);
v = zeros(1,1,n+1);
q(:, :, 1) = q_0;
mu(:, :, 1) = mu_0;
v(:, :, 1) = v_0;

for t = 1:n
```

```

% The SA E-step
if (t == 1)
    % Initial observation
    [filt, T, S_0, S_1, S_2] = ion_e0(Y(1), mu(:, :, 1), v(:, :, 1));
else
    [filt, T, S_0, S_1, S_2] = ...
        ion_e(Y(t), filt, T, S_0, S_1, S_2, q(:, :, t), mu(:, :, t), v(:, :, t), gam(t));
end
% The M-step
if (t >= INHIBIT_LAG)
    [T_a, S_0_a, S_1_a, S_2_a] = ion_e_accum(filt, T, S_0, S_1, S_2);
    [q(:, :, t+1), mu(:, :, t+1), v(:, :, t+1)] = ion_m(T_a, S_0_a, S_1_a, S_2_a);
else
    % Inhibition phase (no update)
    q(:, :, t+1) = q(:, :, t);
    mu(:, :, t+1) = mu(:, :, t);
    v(:, :, t+1) = v(:, :, t);
end
end
end

```

## 2 Subroutines

### 2.1 ion\_e0

```

function [filt, T, S_0, S_1, S_2] = ion_e0(Y, mu, v)

```

```

% ion_e0          Compute the EM auxiliary statistics for the initial data point.
% Use: [filt, T, S_0, S_1, S_2, logl] = ion_e0(Y, mu, v)
% where
%     Y:          initial observation (scalar)
%     mu:          means (m x 1)
%     v:           variance (scalar)
% and
%     filt:        filtering prob. (1 x m)
%     T:           Auxiliary EM transition statistics (m x m x m)
%     S_0:         Auxiliary EM conditional statistics (m x m)
%     S_1:         " (m x m)
%     S_2:         " (m x m)

```

```

% Dimensions
m = length(mu);

```

```

% Likelihood factor
r = exp(-0.5*(Y(ones(m,1)) - mu).^2/v)/sqrt(v);

```

```

% Initial filtering (assuming uniform initial distribution)
c = sum(r);
filt = r/c;

```

```

% Initial statistics
T = zeros(m,m,m);
S_0 = eye(m);
S_1 = eye(m)*Y;
S_2 = eye(m)*Y^2;

```

## 2.2 ion\_e

```

function [filt , T, S_0 , S_1 , S_2] = ...
    ion_e(Y, filt , T, S_0 , S_1 , S_2 , q, mu, v, gam)

% ion_e          Update the auxiliary EM statistics for one data point.
% Use: [filt , T, S_0 , S_1 , S_2] = ...
%   ion_e(Y, filt , T, S_0 , S_1 , S_2 , q, mu, v, gam)
% where
%       Y:      observation (scalar)
%       q:      transition matrix (m x m)
%       mu:     means (m x 1)
%       v:      variance (scalar)
%       gam:    stepsize (scalar)
% and
%       filt:   filtering prob. (1 x m)
%       T:      Auxiliary EM transition statistics (m x m x m)
%       S_0:    Auxiliary EM conditional statistics (m x m)
%       S_1:    " (m x m)
%       S_2:    " (m x m)

% Dimensions
m = length(mu);

% New likelihood factor
r = (filt*ones(1, m)).*q;
joint = r.*(ones(m,1)*(exp(-0.5*(Y(ones(m,1))-mu).^2/v)/sqrt(v))');
% Filtering update
filt = (sum(joint,1))';
c = sum(filt);
% Normalize
joint = joint/c;
filt = filt/c;
% Retrospective kernel
r = r./(ones(m,1)*sum(r));

% Statistics update
T1 = zeros(m,m,m);
for k = 1:m
    T1(:,k,k) = r(:,k);
end
T = gam*T1+(1-gam)*reshape((reshape(T,m*m,m)*r),m,m,m);
S_0 = gam*eye(m)+(1-gam)*(S_0*r);
S_1 = gam*eye(m)*Y+(1-gam)*(S_1*r);
S_2 = gam*eye(m)*Y^2+(1-gam)*(S_2*r);

```

## 2.3 ion\_e\_accum

```

function [T_a, S_0_a , S_1_a , S_2_a] = ion_e_accum(filt , T, S_0 , S_1 , S_2)

% ion_e_accum    Obtain EM statistics from auxiliary statistics.
% Use: [T_a, S_0_a , S_1_a , S_2_a] = ion_e_accum(filt , T, S_0 , S_1 , S_2)
%       filt:    filtering prob. (1 x m)
%       T:       Auxiliary EM transition statistics (m x m x m)

```

```

%      S_0:      Auxiliary EM conditional statistics (m x m)
%      S_1:      " (m x m)
%      S_2:      " (m x m)
% and
%      T_a:      EM transition statistics (m x m x 1)
%      S_0_a:    EM conditional statistics (m x 1)
%      S_1_a:    " (m x 1)
%      S_2_a:    " (m x 1)

```

```

% Dimensions

```

```

m = length(S_0);

```

```

% Weight with filter values

```

```

T_a = reshape((reshape(T,m*m,m)*filt),m,m);
S_0_a = S_0*filt;
S_1_a = S_1*filt;
S_2_a = S_2*filt;

```

## 2.4 ion\_m

```

function [q, mu, v] = ion_m(T, S_0, S_1, S_2);

```

```

% ion_m      The M-step in the ion channel model.

```

```

% Use: [q, mu, v] = ion_m(T, S_0, S_1, S_2)

```

```

% where

```

```

%      T:      EM transition statistics (m x m)
%      S_0:    EM conditional statistics (m x 1)
%      S_1:    " (m x 1)
%      S_2:    " (m x 1)

```

```

% and

```

```

%      q:      transition matrix (m x m)
%      mu:     means (m x 1)
%      v:      variance (scalar)

```

```

% Dimensions

```

```

m = size(T,1);

```

```

% Transition matrix

```

```

q = T./ (sum(T,2)*ones(1,m));

```

```

% Means

```

```

mu = S_1./S_0;

```

```

% Variance

```

```

v = sum(S_2-(S_0.*mu.^2))/sum(S_0);

```