Phan Duong Hieu

Telecom Paris, IPP

Phan Duong Hieu (Telecom Paris)

Cryptography

MICAS 2021 1/59

New Technologies and the Risks for Privacy

Privacy

- Privacy: "the right to be left alone"
- *Privacy protection* allows individuals to have control over how their personal information is collected and used

Big Data, Cloud computing

- Easy to collect and store user data
- Combined with powerful tools (e.g., machine learning)

 \rightarrow Attractive applications but Huge risk of mass surveillance, social credit systems.

Cryptography

Security of Data

- Integrity with hash function
- Confidentiality with encryption
- Authenticity with MAC, signature

New Technologies \rightarrow Advanced cryptographic primitives

- $\bullet\,$ Big Data, Cloud Computing \rightarrow widespread real-life applications
- Privacy: protect personal information.
 - Security
 - Trust on Authorities

\rightarrow Security of Computation on Untrusted Machines.

Documentation:

https://www.di.ens.fr/users/phan/cryptographie.html

Cryptography in Museum of Mathematics



Phan Duong Hieu (Telecom Paris)

Cryptography

► ▲ ■ ▶ ■ • つ Q C MICAS 2021 4/59

・ロト ・四ト ・ヨト ・ヨト

Some directions for the future:

- How to protect privacy in the AI era
- How to protect privacy against powerful adversaries (e.g., anamorphic encryption)
- How to implement the "Right to be Forgotten"
- How to use powerful tools (e.g., quantum machines) to protect data and privacy (e.g., key leasing)

Some directions for the future:

- How to protect privacy in the AI era
- How to protect privacy against powerful adversaries (e.g., anamorphic encryption)
- How to implement the "Right to be Forgotten"
- How to use powerful tools (e.g., quantum machines) to protect data and privacy (e.g., key leasing)

This course

- How new concepts were invented and their impact
- How security can be proven

Public-key Encryption (Diffie-Helmann 1976)

- Encryption key could be published \rightarrow encryption can be publicly computed.
- RSA scheme

 $(m^e)^{(e^{-1} \mod \phi(N))} = m \mod N$, where N = pq

Public-key Encryption (Diffie-Helmann 1976)

- Encryption key could be published \rightarrow encryption can be publicly computed.
- RSA scheme

$$(m^e)^{(e^{-1} \mod \phi(N))} = m \mod N$$
, where $N = pq$

Elgamal scheme

 $\frac{m(g^d)^r}{(g^r)^d} = m$, where g is a generator of a prime-order cyclic group

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

Beyond Encryption:

- Interactive proofs, zero-knowledge proofs, PCP
- Identification, Digital Signature
- Computation on Encrypted Data (Functional Encryption, FHE)
- Decentralized computation/ Verifiable computation (beyond data security)
- Multi-party computation (for doing any cryptographic task imaginable!)

Main Theoretical Question (Complexity)

Does Cryptography really exist?

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

• P: Problems for which solutions can be "efficiently" found

NP: Problems for which solutions can be "efficiently" verified

- ∢ ∃ ▶

- P: Problems for which solutions can be "efficiently" found
- NP: Problems for which solutions can be "efficiently" verified

Efficiency

- Formal definition of algorithm (Turing machine)
- Church-Turing Thesis: everything that nature computes, can be emulated on a Turing machine
- Efficient algorithm: number of basic steps is bounded by a polynome on the size of the input

- P: Problems for which solutions can be "efficiently" found
- NP: Problems for which solutions can be "efficiently" verified

Efficiency

- Formal definition of algorithm (Turing machine)
- Church-Turing Thesis: everything that nature computes, can be emulated on a Turing machine
- Efficient algorithm: number of basic steps is bounded by a polynome on the size of the input
- Example
 - P: multiplication, exponentiation modulo a prime number,...
 - NP: factorisation, discrete logarithm, 3-coloring problem, sodoku,...

• P: Problems for which solutions can be "efficiently" found

• NP: Problems for which solutions can be "efficiently" verified

- ∢ ∃ ▶

- P: Problems for which solutions can be "efficiently" found
- NP: Problems for which solutions can be "efficiently" verified

Definition of an NP Language

A language \mathcal{L} is an NP-language if there is a polynomial-time verifier V such that:

- Completeness: True theorems have (short) proofs.
 For all *x* ∈ *L*, there is a polynomial(|*x*|))-size witness (proof) *w* ∈ {0,1}* such that *V*(*x*, *w*) = 1.
- Soundness: False theorems have no short proofs. For all x ∉ L, there is no witness.
 i.e., for all polynomially long w ∈ {0,1}*, V(x, w) = 0.

(Trapdoor) one-way functions

A function $f : \{0, 1\}^* \longrightarrow \{0, 1\}^*$ is a (trapdoor) function if it is

- Efficiently computable: f(x) is efficiently computable for any $x \in_R \{0, 1\}^n$
- Hard to invert: for a random $x \in_R \{0, 1\}^n$, given y = f(x), it is hard to find a \bar{x} such that $y = f(\bar{x})$

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

(Trapdoor) one-way functions

A function $f : \{0, 1\}^* \longrightarrow \{0, 1\}^*$ is a (trapdoor) function if it is

- Efficiently computable: f(x) is efficiently computable for any $x \in_R \{0, 1\}^n$
- Hard to invert: for a random $x \in_R \{0, 1\}^n$, given y = f(x), it is hard to find a \bar{x} such that $y = f(\bar{x})$: for all PPT adversary *A*:

$$\Pr_{x \in_R\{0,1\}^n} \Big[A\big(1^n, f(x)\big) = x' \text{ et } f(x) = f(x') \Big] \text{ is negligible.}$$

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

(Trapdoor) one-way functions

A function $f : \{0, 1\}^* \longrightarrow \{0, 1\}^*$ is a (trapdoor) function if it is

- Efficiently computable: f(x) is efficiently computable for any $x \in_R \{0, 1\}^n$
- Hard to invert: for a random $x \in_R \{0, 1\}^n$, given y = f(x), it is hard to find a \bar{x} such that $y = f(\bar{x})$: for all PPT adversary *A*:

$$\Pr_{x \in_R\{0,1\}^n} \Big[A\big(1^n, f(x)\big) = x' \text{ et } f(x) = f(x') \Big] \text{ is negligible.}$$

• Trapdoor: given a trapdoor, it is easy to invert the function *f*.

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

MICAS 2021

10/59

(Trapdoor) one-way functions

A function $f : \{0, 1\}^* \longrightarrow \{0, 1\}^*$ is a (trapdoor) function if it is

- Efficiently computable: f(x) is efficiently computable for any $x \in_R \{0, 1\}^n$
- Hard to invert: for a random $x \in_R \{0, 1\}^n$, given y = f(x), it is hard to find a \bar{x} such that $y = f(\bar{x})$: for all PPT adversary *A*:

$$\Pr_{x \in_R\{0,1\}^n} \Big[A\big(1^n, f(x)\big) = x' \text{ et } f(x) = f(x') \Big] \text{ is negligible.}$$

• Trapdoor: given a trapdoor, it is easy to invert the function *f*.

Necessary conditions for the existence of cryptography
 One-way function for secret-key cryptography

(Trapdoor) one-way functions

A function $f : \{0, 1\}^* \longrightarrow \{0, 1\}^*$ is a (trapdoor) function if it is

- Efficiently computable: f(x) is efficiently computable for any $x \in_R \{0, 1\}^n$
- Hard to invert: for a random $x \in_R \{0, 1\}^n$, given y = f(x), it is hard to find a \bar{x} such that $y = f(\bar{x})$: for all PPT adversary *A*:

$$\Pr_{x \in_R\{0,1\}^n} \Big[A\big(1^n, f(x)\big) = x' \text{ et } f(x) = f(x') \Big] \text{ is negligible.}$$

• Trapdoor: given a trapdoor, it is easy to invert the function *f*.

Necessary conditions for the existence of cryptography

- One-way function for secret-key cryptography
- Trapdoor one-way function for public-key cryptography

(Trapdoor) one-way functions

A function $f : \{0, 1\}^* \longrightarrow \{0, 1\}^*$ is a (trapdoor) function if it is

- Efficiently computable: f(x) is efficiently computable for any $x \in_R \{0, 1\}^n$
- Hard to invert: for a random $x \in_R \{0, 1\}^n$, given y = f(x), it is hard to find a \bar{x} such that $y = f(\bar{x})$: for all PPT adversary *A*:

$$\Pr_{x \in_R\{0,1\}^n} \Big[A\big(1^n, f(x)\big) = x' \text{ et } f(x) = f(x') \Big] \text{ is negligible.}$$

• Trapdoor: given a trapdoor, it is easy to invert the function *f*.

Necessary conditions for the existence of cryptography

- One-way function for secret-key cryptography
- Trapdoor one-way function for public-key cryptography

5 Worlds in Impagliazzo's view

W1-Algorithmica: P = NP

One could use the method of verifying the solution to automatically solve the problem!

5 Worlds in Impagliazzo's view

W1-Algorithmica: P = NP

One could use the method of verifying the solution to automatically solve the problem!

W2-Heuristica: NP problems are hard in the worst case but easy on average.

There exist hard instances of NP problem, but to find such hard instances is itself a hard problem.

5 Worlds in Impagliazzo's view

W1-Algorithmica: P = NP

One could use the method of verifying the solution to automatically solve the problem!

W2-Heuristica: NP problems are hard in the worst case but easy on average.

There exist hard instances of NP problem, but to find such hard instances is itself a hard problem.

W3-Pessiland: NP problems hard on average but no one-way functions exist

It's easy to generate many hard instances of NP-problems, but no way to generate hard instances where we know the solution.

5 Worlds in Impagliazzo's view (cont.)

Minicrypt: One-way functions exist but public-key cryptography does not exist.

• • • • • • • • • • • • •

Minicrypt: One-way functions exist but public-key cryptography does not exist.

Cryptomania: Public-key cryptography is possible

It is possible for two parties to agree on a secret message using only public accessible channels

Phan Duong Hieu (Telecom Paris)

Cryptography

MICAS 2021 12/59



2

イロン イロン イヨン イヨン

(Zero-knowledge) Interactive Proof: Idea

Interactive proofs [Goldwasser, Micali, Rackoff '85]

"A proof is whatever convinces me" (Shimon Even)

Zero-knowledge proofs: the verifier gets no information

- A toy example: Distinguishing the wines of Bordeaux and Côtes du Rhone
- ZKP for all NP problems (Goldreich-Micali-Wigderson '91)
 - Verifier is poly-time TM, Prover could be all powerful
 - Exemple: Graph non-isomorphism
 - Simulation (zero-knowledge)
- Zero-knowledge proof of knowledge.
 - Verifier is poly-time TM, Prover is often poly-time TM as well
 - Simulation (zero-knowledge) + Extraction (proof of knowledge)

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

Interactive Proofs



 \mathcal{L} is an **IP-language** if there is a **probabilistic poly-time** verifier V:

• Completeness: If $x \in \mathcal{L}$,

$$\Pr[(P, V)(x) = \operatorname{accept}] = 1.$$

• Soundness: If $x \notin \mathcal{L}$, for every P^* ,

 $Pr[(P^*, V)(x) = accept]$ is negligible.

Zero-knowledge Proof: Simulator



Phan Duong Hieu (Telecom Paris)

Cryptography

MICAS 2021 16/59

э

Zero-knowledge Proof of Knowledge: Extractor



Phan Duong Hieu (Telecom Paris)

Cryptography

MICAS 2021 17/59

Zero-knowledge Proof of Knowledge on DL

Zero-knowledge

DL Assumption: $G = \langle g \rangle$, given $h = g^x$, it is hard to compute *x*. ZKP: Given *g* and $h = g^x$, I can convince you that I know *x* without revealing it.



In a group $\mathbb{G} = \langle g \rangle$ of prime order q, the **DDH**(g, h) assumption states it is hard to distinguish

$$\mathcal{L} = (u = g^x, v = h^x)$$
 from $\mathcal{G}^2 = (u = g^x, v = h^y)$

 $\mathcal P$ knows x, such that $(u = g^x, v = h^x) \in \mathcal L$ and wants to prove it to $\mathcal V$

Zero-Knowledge Proof for DDH



MICAS 2021 20/59

Completeness and Soundness

Completeness

 Definition (recall): If the prover knows the secret *x* such that (*u* = *g^x*, *v* = *h^x*) ∈ *L* and follows the protocol correctly, the verifier will always accept the proof.

• **Indeed:** If \mathcal{P} knows *x*, both checks will hold and the verifier will accept the proof.

Soundness

- Definition (recall): If the statement is false (i.e., (u = g^x, v = h^{x'}) ∉ L, x ≠ x'), no prover can convince the verifier except with negligible probability.
- **Indeed:** The prover can consistently compute *a* that satisfies both conditions: $U = g^r = g^a u^b$ and $V = h^{r'} = h^a v^b$, which implies r r' = b(x x'), for random *b* with probability 1/q, which is negligible:

・ロト ・ 四ト ・ ヨト ・ ヨト … ヨ

Zero-knowledge Proof: Simulator

Definition: The verifier learns nothing beyond the validity of the statement.

Simulator Construction:

- Simulator selects a random b ∈ Z_q and a ∈ Z_q.
 Computes U = g^au^b and V = h^av^b.
- Output (a, b, U, V).

Indistinguishability:

- Verifier cannot distinguish between real and simulated interactions.
- Transcripts are statistically indistinguishable.

< □ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □

Extractor

- Extractor Role: To show that the prover knows *x*, an extractor can derive *x* from multiple valid responses.
- Extractor Construction:

• For fixed (U, V), two valid answers *s* and *s'* satisfy:

$$g^{s}u^{h} = U = g^{s'}u^{h'}$$

 $h^{s}v^{h} = V = h^{s'}v^{h'}$

If one sets y such that:

$$(s-s')(h'-h)^{-1} \mod q$$

This implies:

$$u = g^y$$
 and $v = h^y$

• **Conclusion:** The existence of the extractor confirms that the prover knows *x*.

Phan Duong Hieu (Telecom Paris)

Cryptography

MICAS 2021 23/59
Zero-Knowledge Proof for DDH: Malicious Verifier



MICAS 2021 24/59

Zero-Knowledge Proof: Simulator

• **Definition:** The verifier learns nothing beyond the validity of the statement.

Simulator Construction:

- Simulator selects a random $\mathbf{b}' \in \{\mathbf{0}, \mathbf{1}\}^t$ (recall that *t* is small so that $2^t \in poly(\log q)$) and $a' \in \mathbb{Z}_q$.
- 2 Computes $U = g^{a'}u^{b'}$ and $V = h^{a'}v^{b'}$.
- Sends (U, V) to the verifier.
- Verifier sends back a challenge $b \in \{0, 1\}^t$.
- **(**) If b = b', simulator sets a = a' and outputs (a, b, U, V)
- **(b)** If $b \neq b'$, simulator restarts.

Indistinguishability:

- Verifier cannot distinguish between real and simulated interactions.
- Transcripts are statistically indistinguishable.
- **Conclusion:** The proof is zero-knowledge as the verifier learns nothing about *x*.

Minicrypt: Commitment

- Alice commits herself to some message *m* by giving Bob:
 c = Commit(*m*, *r*), for a ramdom *r*.
- Bob should not learn anything about *m* given the commitment *c*.
- Alice can **open** the commitment by giving (m, r) to Bob to convince him that *m* was the value she committed herself to.

Two properties:

- Hiding Commitment c hides information on m
- Binding Alice cannot open c to $(m', r') \neq (m, r)$

Example & Application

- Pederson's construction
- General construction from one-way function
- \rightarrow In Minicrypt: ZKP for all NP problem (on ZKP for G3C)

ヘロト 人間 とくほ とくほ とう

ZKP in Practice: Privacy in Blockchain

A Bitcoin tr	ransaction					
	O es243fed3a6788632ee2b2dda4e19e1b395e4f3e180ec3a000e582e86b9a2488			min	ed Oct 2, 2017 7:48:22 PM	
	TAPBSSINBKNEZSBEITH CHOVYBEZ7KINNVYIQ7	0.5 BTC	Ť	17k292prL2n3QJB2N93QLSMB9KLEQNYVEZL	0.2485 BTC (0)	
	FEE: 0.0015 BTC			35 CONFIRMATIO	0.4985 BTC	
	17d910d6ar189a597eb70492f297ebc4a9ae623a75f82 1ArB35n8kNt236fh1CHcvYaEz7RnnV9qq7	0.5 BTC	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	min 1CBk5dAsbC3ZzDSLC2nBq9kYXjfvQkSWGZ	0.25 BTC (5)	
	FEE: 0.0015 BTC			18ojbg2ZkaKjvyWyBousuFvXqp1WGj4wbQ 3s CONFRMATIC	0.2485 BTC (U)	

Privacy

- What is the problem with privacy in bitcoin?
- How we can use ZKP to solve this? \rightarrow zkSNARKS.

3

< ロ > < 同 > < 回 > < 回 >

Signatures/Commitment in Practice

(beyond classical examples)

C2PA and the need of Short Polynomial Commitment



Content Provenance and Authenticity

An open technical standard providing publishers, creators, and consumers the ability to trace the origin of different types of media.

Polynomial Commitment

Given a polynomial $P(x) = \sum_{i=0}^{n-1} a_i x^i$. We want the sender to commit *P* in such a way that it can prove to the receiver that (u, v) satisfies: P(u) = v.

- Inear-size commitment: exercice
- constant-size commitment: KZG10, using pairings

KZG10 Polynomial Commitment: Setup

Setup:

- Select a prime field 𝔽_p and a generator g of a group 𝔅 of prime order p.
- 2 Choose a random $s \in \mathbb{F}_{p}$.
- Sompute $\{g_0 = g, g_1 = g^s, g_2 = g^{s^2}, \dots, g_d = g^{s^d}\}$ for a polynomial of degree *d*.
- Publish the setup parameters $PP = \{g_0, g_1, g_2, \dots, g_d\}$.
- **Trusted Setup Assumption:** The trusted setup randomly generates *s*, compute {*g*₀, *g*₁, *g*₂, ..., *g*_d}, then erase *s*.

KZG10 Polynomial Commitment: Commitment

- **Polynomial:** $P(x) = a_0 + a_1x + a_2x^2 + \dots + a_dx^d$
- Commitment:

$$egin{array}{rcl} \mathcal{C} &=& g_0^{a_0} \cdot g_1^{a_1} \cdot g_2^{a_2} \cdot \cdots \cdot g_d^{a_d} \ &=& g^{a_0} \cdot (g^s)^{a_1} \cdot (g^{s^2})^{a_2} \cdot \cdots \cdot (g^{s^d})^{a_d} \ &=& g^{\mathcal{P}(s)} \end{array}$$

• **Result:** The commitment *C* is a single group element in G.

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

KZG10 Polynomial Commitment: Opening

• Opening:

- To open the commitment at point x = u, compute the evaluation v = P(u).
- u is a root of P(x) v.
- We can write thus P(x) v = (x u)Q(x) and can compute Q(x).
- Generate proof $\pi = g^{Q(s)}$.
- Send to Verifier: $\{u, v, \pi\}$

KZG10 Polynomial Commitment: Verification

Verification:

- Verifier receives $\{u, v, \pi\}$ and the commitment *C*.
 - IDEA: Check at the random point s if P(s) v = (s u)Q(s)
- This check can only performed with a pairing e : G × G → G_T
 Compute:

$$e(g_1g^{-u},\pi)\stackrel{?}{=}e(g,Cg^{-v})$$

 Result: If the equality holds, the proof is valid and the polynomial evaluates to v = P(u) at point u. If one-way functions exist, then every NP problem has a zero-knowledge proof. [Goldreich, Micali, Wigderson 91]

From zero-knowledge proof to digital signature (Schnorr scheme)

Given g and $y = g^x$, sign on the message m with the secret key x

- I take a random r and send to you g^r
- k is set to be $H(g^r, m)$ (H is modeled as a random oracle)
- I finally send to you the signature $(m, g^r, t = r kx)$.
- Verification: checking whether $g^r = g^t y^{H(g^r,m)}$

In Random Oracle Model

If one-way functions exist, then one can construct digital signature.

Minicrypt

- Zero-knowledge proofs, Identification, Digital Signature inspire from the notion of PKE.
- However, even if PKE dies one day, the above primitives would still be alive!

Digital Signatures: Formal Treatment

A signature scheme S = (G, S, V):

- Key Generation: G(1^λ) → (pk, sk) is a probabilistic algorithm that takes a security parameter λ and outputs a secret signing key sk and a public verification key pk.
- Signing: S(sk, m) → σ is a probabilistic algorithm that outputs a signature σ.
- Verification: V(pk, m, σ) outputs either accept (1) or reject (0).

We require that a signature generated by S is always accepted by V:

 $\Pr[V(pk, m, S(sk, m)) = \operatorname{accept}] = 1$

Digital Signatures: attack model (EUF-CMA)



Existential unforgeability under adaptive chosen message attacks

```
Adv(\mathcal{A}) = \Pr[Vfy(pk, m^*, \sigma^*) = 1]
```

The scheme is EUF-CMA secure si $\forall A, Adv(A)$ is negligible.

Lamport's One-time Signatures from OWF f

• Gen
$$(1^{\lambda})
ightarrow (pk, sk)$$
:

$$sk = \begin{pmatrix} x_{1,0} & x_{2,0} & \cdots & x_{\ell,0} \\ x_{1,1} & x_{2,1} & \cdots & x_{\ell,1} \end{pmatrix}$$
$$pk = \begin{pmatrix} y_{1,0} & y_{2,0} & \cdots & y_{\ell,0} \\ y_{1,1} & y_{2,1} & \cdots & y_{\ell,1} \end{pmatrix}$$
where $x_{i,b} \in \{0,1\}^n, y_{i,b} = f(x_{i,b})$

•
$$Sign(sk, m = m_1 m_2 \dots m_\ell \in \{0, 1\}^\ell) \to \sigma$$

$$\sigma = \mathbf{X}_{1,m_1} \mathbf{X}_{2,m_2} \dots \mathbf{X}_{\ell,m_\ell}$$

• Vfy(pk, m,
$$\sigma$$
) check if $y_{i,m_i} = f(\sigma_i = x_{i,m_i}), \forall i = 1 \dots \ell$

Theorem

If f is one-way, then the one-time signature is EUF-CMA.

Phan Duong Hieu (Telecom Paris)

Complete proof: $OWF \rightarrow Digital Signature$

Complete proof: $\text{OWF} \rightarrow \text{Digital Signature}$

- 1-time signature \rightarrow Stateful 2-time signature \rightarrow Stateful poly-time signature
- Stateful to Stateless with PRF
- Sign on a long message → short message by using a hash function.

Exercice:

Given:

- a collision resistant hash function $H : \{0,1\}^* \to H : \{0,1\}^n$
- a EUF-CMA singature on message of n bits

Construct another EUF-CMA singature that can sign on messages of abitrary size.

FDH - RSA

FDH - RSA

- $Gen(1^{\lambda}) \rightarrow (sk = d, pk = (N, e))$ as in RSA
- $Sign(sk, m) \rightarrow \sigma = H(m)^d$, where H is a random oracle.
- Verfy(pk, m, σ) accept iff $\sigma^e = H(m)$

Security of FDH - RSA

If RSA problem is hard then FDH - RSA is EUF-CMA secure. Proof: reading exercice.

Signature Schemes in Practice

		Key exchange			Signatures			
	Hosts	RSA	DH	ECDH	RSA	DSA	ECDSA	
HTTPS	39M	39%	10%	51%	99%	pprox 0	1%	
SSH	17M	pprox 0	52%	48%	93%	7%	0.3%	
IKEv1	1.1M	-	97%	3%	-	-	-	
IKEv2	1.2M	-	98%	2%	-	-	-	

イロト イヨト イヨト イヨト



イロン イロン イヨン イヨン

Provable security: sufficient conditions for security

What we discussed

If factorization or DL problems are easy, then we can attack crypto systems (RSA, ElGamal) that based on these problems

Question

Suppose that factorization and DL problems are hard. Could we prove the security for proposed crypto systems?

< ロ > < 同 > < 回 > < 回 >

One wayness is enough?

 $E'(m1||m_2) := E(m_1)||m_2|$

- If E is one-way, then E' is also one-way
- But the security of E' is clearly not enough: at least half the message leaks!

In many situation, one bit (attack or not) is important...



Phan Duong Hieu (Telecom Paris)

Cryptography

Semantic security [Goldwasser-Micali '82]

Perfect Security vs. Semantic security

- Perfect security: the distribution of the ciphertext is perfectly independent of the plaintext
- Semantic security (computational version of perfect security): the distribution of the ciphertext is computationally independent of the plaintext

• • • • • • • • • • • •

Perfect Security vs. Semantic security

- Perfect security: the distribution of the ciphertext is perfectly independent of the plaintext
- Semantic security (computational version of perfect security): the distribution of the ciphertext is computationally independent of the plaintext

Semantic Security - IND

 Semantic Security is equivalent to the notion of Indistinguishability (IND): No adversary (modeled by a poly-time Turing machine) can distinguish a ciphertext of m₀ from a ciphertext of m₁.

イロト 不得 トイヨト イヨト

IND Security Notion

IND:

Security Game:



- 2 A random bit $b \in \{0, 1\}$ is selected, and the challenger encrypts m_b to get the ciphertext $c = \text{Enc}(pk, m_b)$.
- 3 The ciphertext c is given to \mathcal{A} .
- ④ \mathcal{A} outputs a guess $b' \in \{0, 1\}$.
- Advantage:

$$\mathsf{Adv}_{\mathcal{A}}^{\mathsf{IND-CPA}} = \left|\mathsf{Pr}[b'=b] - \frac{1}{2}\right|$$

IND-CPA Security:

 \forall polynomial-time \mathcal{A} , Adv^{IND-CPA} is negligible

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

Security of RSA & ElGamal PKE

Recall:

- k_e could be published \rightarrow encryption can be publicly computed.
- RSA scheme

 $(m^e)^{(e^{-1} \mod \phi(N))} = m \mod N$, where N = pq

< ロ > < 同 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ >

Security of RSA & ElGamal PKE

Recall:

- k_e could be published \rightarrow encryption can be publicly computed.
- RSA scheme

 $(m^e)^{(e^{-1} \mod \phi(N))} = m \mod N$, where N = pq

ElGamal scheme

$$\frac{m(g^d)^r}{(g^r)^d} = m$$
, where g is a generator of a cyclic group

Exercices

Is RSA IND? Is ElGamal IND?

Security of RSA & ElGamal PKE

Recall:

- k_e could be published \rightarrow encryption can be publicly computed.
- RSA scheme

 $(m^e)^{(e^{-1} \mod \phi(N))} = m \mod N$, where N = pq

ElGamal scheme

$$\frac{m(g^d)^r}{(g^r)^d} = m$$
, where g is a generator of a cyclic group

Exercices

- Is RSA IND? Is ElGamal IND?
- For public-key encryption: Probabilistic encryption is required!
- For secret-key encryption: deterministic encryption could be semantically secure [Phan-Pointcheval '04]

Phan Duong Hieu (Telecom Paris)

Cryptography

Semantic security/IND is enough?

ElGamal Encryption

- Elgamal encryption can be proven to be IND, based on Decisional Diffie-Hellman assumption (given g^a, g^b , it is hard to distinguish between g^{ab} and a random element g^z).
- Elgamal encryption is homomorphic: $E(m_1m_2) = E(m_1)E(m_2)$

Private Auctions

The bids are encrypted. The authority then opens all the encrypted bids and the highest bid wins

- IND guarantees privacy of the bids
- Malleability: from c = E(pk, b), without knowing *b*, one can generate c' = E(pk, 2b): an unknown higher bid!
- Should consider adversaries with some more information.

イロト 不得 トイヨト イヨト

Adversaries with additional information

Rosetta Stone: A key element to decode Ancient Egyptian hieroglyphs



Chosen plaintext attacks (CPA)

The adversary can have access to encryption oracle (this only makes sense for symmetric encryption)

Phan Duong Hieu (Telecom Paris)

Cryptography

MICAS 2021 48/59

• • • • • • • • • • • •

Interactive Adversaries: CCA attacks



Phan Duong Hieu (Telecom Paris)

イロト イロト イヨト イヨト

IND-CCA Security Notion in Encryption

• IND-CCA Security Game:

- The adversary A is given pk and also given access to an oracle that decrypts ciphertexts.
- 2 \mathcal{A} chooses two plaintexts m_0 and m_1 .
- Solution A random bit $b \in \{0, 1\}$ is selected, and the challenger encrypts m_b to get the challenge ciphertext $c^* = \text{Enc}(pk, m_b)$.
- The ciphertext c^* is given to A.
- A continues to have access to the decryption oracle, except for the challenge ciphertext (*i.e.*, cannot query c*). (*)
- \mathcal{A} outputs a guess $b' \in \{0, 1\}$.

Advantage:

$$\mathsf{Adv}_{\mathcal{A}}^{\mathsf{IND}\operatorname{-}\mathsf{CCA}} = \left|\mathsf{Pr}[b'=b] - \frac{1}{2}\right|$$

• IND-CCA Security:

 $\forall \text{polynomial-time } \mathcal{A}, \text{Adv}_{\mathcal{A}}^{\text{IND-CCA}} \text{ is negligible}$

CCA1: CCA without access to the decryption oracle in the second phase (*)

Phan Duong Hieu (Telecom Paris)

Chosen plaintext and chosen ciphertext attacks

IND-CCA Security

- IND-CCA also implies non-malleability (NM-CCA)
- This is the standard notion for public-key encryption
- Exercice: Is ElGamal IND-CCA?

Major problem in cryptography

Construction of IND-CCA encryption schemes.

OAEP (Bellare-Rogaway94)





- It is believed that f-OAEP is IND-CCA for any trapdoor one-way permutation.
- In 2000, Shoup presented an attack on a very special trapdoor one-way permutation.

Phan Duong Hieu (Telecom Paris)

RSA-OAEP



RSA-OAEP is proven IND-CCA secure [Fujisaki-Okamoto-Pointcheval-Stern01]

- If f is partially one-way, then f-OAEP is secure
- RSA is partially one-way

Phan Duong Hieu (Telecom Paris)

Cryptography

MICAS 2021 53/59

3-round OAEP (among others varieties of OAEP)



F, G, H: fonctions aléatoires

Advantages

- f does not need to be partially one-way
- f could also be one-way function (such as Elgamal, Paillier encryptions...)

A (10) A (10)

3-round OAEP (among others varieties of OAEP)



F, G, H : fonctions aléatoires

Advantages

- f does not need to be partially one-way
- *f* could also be one-way function (such as Elgamal, Paillier encryptions...)

Current state

Many solutions in the standard model (without random oracle) but the practical implementations mostly rely on RSA-OAEP.

Phan Duong Hieu (Telecom Paris)

Cryptography

Proof of IND-CPA of ElGamal scheme, under DDH assumption

Let $\mathbb{G} = \langle g \rangle$ with generator g of order $|\mathbb{G}| = q$ where q is a prime. Public key $pk = (g, h = g^x)$ and secret key sk = x. Encryption:Enc $(pk, m) = (g^r, h^r \cdot m)$ where $r \leftarrow \mathbb{Z}_q$.

- Game 0: Real IND-CPA game, challenge ciphertext is $(g^r, h^r \cdot m_b)$
- **Game 1:** Replace (g, h, g^r, h^r) by $(g, h, g^r, h^{r'})$, for random r, r'The adversary cannot distinguish Game 0 and Game 1, otherwise we can solve DDH
- In Game 1: the adversary has no information about m_b.
Security Proofs: IND-CCA

Idea: Embed a ZK proof of knowledge for a DDH tuple in the ciphertext.

- Let $\mathbb{G} = \langle g \rangle$ with generator g of order $|\mathbb{G}| = q$ where q is a prime.
- Verifier chooses α, x₁, x₂ ← Z_q and sets g₁ = g, g₂ = g^α, c = g₁^{x₁}g₂^{x₂} and sends g₁, g₂, c to prover.
- Prover chooses $r \leftarrow \mathbb{Z}_q$, sets $u_1 = g_1^r, u_2 = g_2^r$ and $v = c^r$
- Verifier checks whether $v = u_1^{x_1} u_2^{x_2}$.

Lemma

It is hard for the prover to return $u_1 = g_1^{r_1}$, $u_2 = g_2^{r_2}$ and v such that $r_1 \neq r_2$ and pass the check of the verifier:

$$v = u_1^{x_1} u_2^{x_2}$$

Proof: exercice

Phan Duong Hieu (Telecom Paris)

イロト 不得 トイヨト イヨト 二日

Security Proofs: IND-CCA

Idea: Embed a ZK proof of knowedge in the ciphertext.

- Let $\mathbb{G} = \langle g \rangle$ with generator g of order $|\mathbb{G}| = q$ where q is a prime.
- Verifier chooses α , x_1 , $x_2 \leftarrow \mathbb{Z}_q$ and sets $g_1 = g$, $g_2 = g^{\alpha}$, $c = g_1^{x_1} g_2^{x_2}$ and sends g_1, g_2, c to prover.
- Prover chooses $r \leftarrow \mathbb{Z}_q$, sets $u_1 = g_1^r, u_2 = g_2^r$ and $v = c^r$
- Verifier checks whether $v = u_1^{x_1} u_2^{x_2}$.

Cramer-Shoup Lite scheme (IND-CCA1)

Public key $pk = (c = g_1^{x_1} g_2^{x_2}, h = g_1^z)$ and secret key $sk = (x_1, x_2, z)$. Encryption: Enc $(pk, m) = (u_1 = g_1^r, u_2 = g_2^r, e = h^r \cdot m, v = c^r)$ where $r \leftarrow \mathbb{Z}_q$. Decryption: Check if $v = u_1^{x_1} u_2^{x_2}$, return $\frac{e}{u_r^2}$, otherwise return \perp

イロト 不得 トイヨト イヨト 二日

Security Proofs: IND-CCA1 for Cramer-Shoup Lite

Cramer-Shoup Lite scheme (IND-CCA1)

Public key $pk = (c = g_1^{x_1} g_2^{x_2}, h = g_1^z)$ and secret key $sk = (x_1, x_2, z)$. Encryption: Enc $(pk, m) = (u_1 = g_1^r, u_2 = g_2^r, e = h^r \cdot m, v = c^r)$ Decryption: Check if $v = u_1^{x_1} u_2^{x_2}$, return $\frac{e}{u_r^2}$, otherwise return \bot

Game 0:

- Choose x_1, x_2, z , sets : $c = g_1^{x_1} g_2^{x_2}, \quad h = g_1^z$
- For a decryption query (u_1, u_2, e, v) : check $v \stackrel{?}{=} u_1^{x_1} u_2^{x_2}$, if yes $m = \frac{e}{a_r^2}$
- Adv chooses m_0, m_1 , generates challenge $(g_1^r, g_2^r, e = h^r m_b, v = c^r)$

Game 1:

- Choose z_1, z_2 instead of z, sets : $h = g_1^{z_1} g_2^{z_2}$
- check $v \stackrel{?}{=} u_1^{x_1} u_2^{x_2}$, if yes $m = \frac{e}{u_1^{x_1} u_2^{x_2}}$
- generates challenge $(g_1^r, g_2^r, e = u_1^{z_1} u_2^{z_2} m_b, v = c^r)$
- Game 2: Challenge := $(g_1^{r_1}, g_2^{r_2}, e = u_1^{r_1}u_2^{r_2}m_b, v = u_1^{r_1}u_2^{r_2})$.

Exercice: Homomorphism of ElGamal encryption

Let $\mathbb{G} = \langle g \rangle$ with generator g of order $|\mathbb{G}| = q$ where q is a prime. Public key $pk = (g, h = g^x)$ and secret key sk = x. Encryption: Enc(pk, m) = (g^r , $h^r \cdot m$) where $r \leftarrow \mathbb{Z}_q$.

- Given a public key pk and an ciphertext c, show how to create a ciphertext c' which encrypts the same message under pk but with independent randomness.
- Given a public key *pk* and any two independently generated ciphertexts *c*₁, *c*₂ encrypting some unknown messages *m*₁, *m*₂ ∈ G under *pk*, create a new ciphertext *c*^{*} encrypting *m*^{*} = *m*₁ · *m*₂ under *pk* without needing to know *sk*, *m*₁, *m*₂.

Application: Voting system.

イロト 不得 トイヨト イヨト 二日